


Hand Operated Curtain Track Systems




m





Hand Operated Curtain Track System


Silent Gliss® 6243



Product Information

- Single channel curtain track for medium to heavy weight contract applications.
- Thin and bendable recess profile with 5.4mm gliding channel.
- Minimum bending radius 25cm.
- Punched every 200mm.
- Supplied in white as standard.
- Standard profile length is 6m (connecting bridge available for longer lengths).
- Can be bent.
- Available with Wave curtain heading systems.

Profile and Bending Information



6243




Min. radius 25cm

Specification Guide

Silent Gliss 6243 curtain track, hand-drawn, anodised aluminium, complete with gliders 6096 at 16/m. 1 end stop 6065 and 1 spring stop 6053 per length. Top fixed with punched holes every 200mm.


Fitting Information

Fixing points



The fixing distances are meant as a guide only: they may vary in practice depending on surface and curtain weight.

Stack Depth Wave Standard



a = Stack depth
b = Stack size
c = Min. distance

Glider-cord spacing	Curtain hook spacing	Approx. curtain fullness	Stack depth (a)	Stack width (b)	Min distance (c)
6	10	2.1	10	23 per metre of track + endpiece	8
6	12	2.3	12	23 per metre of track + endpiece	9
8	14	2.1	14	18 per metre of track + endpiece	10
8	16	2.3	16	18 per metre of track + endpiece	11

Wave standard with roller gliders


Glider-cord spacing	Curtain hook spacing	Approx. curtain fullness	Stack depth (a)	Stack width (b)	Min distance (c)
8	14	2.1	14	21 per metre of track + endpiece	10
8	16	2.3	16	21 per metre of track + endpiece	11

(dimensions in cm)

Note: Minimum distance (c) includes a standard 3cm clearance (front and back).

System Options

Wave Standard curtain heading system



Wave is an exciting new contemporary curtain heading system which allows curtains to hang in a continuous wave which is smooth, simple and elegant.

When using the Wave curtain heading system please note that the maximum recommended curtain weight is 2.5kg/m or 10kg/m with wave roller glider 6098W.

The Wave Standard components are:

6345 Glider-cord 60mm
6346 Glider-cord 80mm
6007 End stop

The items listed below are all supplied at an additional cost as per the price list:


Wave hardware components for Enhanced Wave (80mm glider cord only) are:

2255 Adjustable brake
6364 Extension (used with 6365)
6365 Hanger (used with 6364)
6366 Carrier for draw rod

Roller gliders 6098W must be ordered separately:

Optional enhanced components to improve the presentation of the curtain:


3582 Hook
6349 Wave curtain tape
6363 Iron on top hemming tape
10075 Lead weight for hem of curtain 50 gr/m
10076 Fabric weight for side edge of curtain



Fitting Options

CAD download through Silent Gliss e-catalogue

Recess ceiling fix





The final distances from the wall depend on curtain weight, make-up and any obstructions. The profile is punched every 200mm.



Standard Accessories

0240 Screw


6053 Spring stop





6065	Twist eye endstop	
6243	Profile	


6096	Glider 6083 in strip form	
7002	Profile protector	


Optional Accessories


2255	Adjustable brake	
------	------------------	---

3067	Connecting bridge	
------	-------------------	---

3582	Hook	
------	------	---

6057	Hook	
------	------	---


6083	Glider	
------	--------	---


6086	Spring stop	
------	-------------	---


6096	Glider 6083 in strip form	
------	---------------------------	---


6345	Wave glider cord (60mm)	
------	-------------------------	---


6346	Wave glider cord (80mm)	
------	-------------------------	---


6349	Curtain tape	
------	--------------	---


6363	Top hemming tape	
------	------------------	--


6364	Extension	
------	-----------	--

6365	Hanger	
------	--------	---

6366	Wave carrier for draw rod	
------	---------------------------	---

10075	Lead weight 50 gr/m	
-------	---------------------	---

10076	Fabric weight	
-------	---------------	---

6098W	Wave roller glider cord (80mm)	
-------	--------------------------------	---

--	--	--

nm
6243



6243

www.bradingfabrication.com

Brading Fabrication Limited
1885 Clements Road, Unit 228
Pickering, ON, Canada
L1W 3V4

Tel: 289-372-3014

info@bradingfabrication.com